

[www.denverrope.com](http://www.denverrope.com)

For customer service and inquiries please call John 303-809-7274 or email [john@denverrope.com](mailto:john@denverrope.com).

Please email the completed worksheet back to John of Denver Rope or can fax to 305-635-0530 attention Cari Valdes – Denver Rope.

## Denver Rope - Tow Bridle / Tow Line Worksheet

- Working Load: For Ocean and Commercial Towing Application the W.L. is chosen to be equal to the fully loaded weight of the towed vessel as a minimum. For in-land / light duty / pleasure marine / lake applications the W.L. is often chosen to be 1/3 – 1/2 the fully loaded weight of the towed vessel.
- Denver Rope is always concerned as not to exceed a customer's budget. However, the Captain is legally responsible for the safety of his crew and equipment; therefore, it is always better to error on the conservative side when specifying a Tow Bridle / Tow Line.
- Use sections C-F to specify a single leg tow line / mooring pendant / other.
- Please fill out this worksheet the best you can and return to Denver Rope. Thank you.

Please describe below your towing vessel and the towed vessel below. Include weight, location, etc.

---

---

---

Please describe below what you are specifying on this worksheet; Y tow bridle, single leg tow line, mooring pendant, hawser line, anchor line, mooring line, other.

---

---

---






36" Covered Eye Splice



Y-Point with stern legs to the right and tow leg the left



Tow Leg with a Safety Bolted



Snubber with Bow Shackle



Swivel Eye Hook and Bow Shackle




Quick Release Snap Shackle



Trigger Release Shackle

**B2.** Eye Splices are hand sewn & whipped, and made-to-order



**B1.** Y Bitter Ends melted clean & whipped, and hand

**A.** Stern Legs

**C.** Y — Point Connection

**D.** Tow Leg



Optional Lock-On Rope Floats

**E.** Tow Leg Connection

**F.** Tow Leg/Bow Hardware

**G.** Snubber Connection — Tow Leg

**H.** Snubber

**I.** Snubber Connection — Bow

**J.** Bow Hardware

**A. Stern Legs**

1. Specify Length \_\_\_\_\_ (40ft is typical – custome specified)

2. Specify Material \_\_\_\_\_ (double braid nylon is standard)

We will assist the customer in selecting the diameter of rope that matches the W.L. of the line.

**B. Stern Connection (choose between 1 or 2 below)**

1. Specify Bitter Ends \_\_\_\_\_ (y/n - standard)

2. Specify Eye Splice \_\_\_\_\_ (y/n – customer specified below)

a. Eye Splice Size \_\_\_\_\_ (18”, 24” are typical)

b. Chafe Guard \_\_\_\_\_ (y/n - covered eyes are recommended)

**C. Y-Point Connection (choose between 1 or 2 below)**

1. Specify Small Covered Eye Splices \_\_\_\_\_ (y/n – standard - recommended)

a. Eye Splice Size \_\_\_\_\_ (9”, 12”, 18”, 24” are typical)

b. Chafe Guard \_\_\_\_\_ (y/n - covered eyes are recommended)

2. Hardware Connection \_\_\_\_\_ (y/n - customer specified below)

---

---

---

Some customers may want to disassemble their tow bridle at the Y-Point. Therefore, choose from a combination of the following stainless steel hardware; thimbles, bow or bolted shackles, quick release snap shackles, trigger release shackles, and or a master link. As the working load of the tow bridle increases, the price of this hardware accelerates.

**D. Tow Leg**

1. Specify Length \_\_\_\_\_ (75-200ft is typical – customer specified)

2. Specify Material \_\_\_\_\_ (customer specified)

We will assist the customer in selecting the diameter of rope that matches the W.L. of the line.

Choose double braid nylon for smaller working loads typically equating to rope not much more than 3/4” to 1-0” in diameter. For larger working loads switch rope material to high performance 12-strand dyneema / am-steel rope as it is much lighter, stronger, and it floats.

\* Note: Can add optional rope floats to parts A and or D \*

**E. Tow Leg Connection (choose between 1 or 2 below)**

1. Hard Eye \_\_\_\_\_ (y/n - standard)

a. Light Duty s/s Thimble \_\_\_\_\_ (std for recreational lake applications)

b. Heavy Duty s/s Thimble \_\_\_\_\_ (std for commercial and ocean applications)

2. Soft Eye \_\_\_\_\_ (y/n – customer specified below)

a. Eye Splice Size \_\_\_\_\_ (18”, 24” are typical)

b. Chafe Guard \_\_\_\_\_ (y/n - covered eyes are recommended)

**F. Tow Leg / Bow Hardware (choose from stainless steel hardware listed below)**

1. Bow Shackle \_\_\_\_\_ (y/n)

2. Bolted Safety Shackle \_\_\_\_\_ (y/n)

3. Swivel Eye Hook \_\_\_\_\_ (y/n)

4. Quick Release Snap Shackle \_\_\_\_\_ (y/n)

5. Trigger Release Shackle \_\_\_\_\_ (y/n)

6. Omit Hardware Connection \_\_\_\_\_ (y/n, typ if E2 selected and single legged)

We will assist the customer in selecting the hardware that matches the W.L. of the line.

**\* Denver Rope Optional Item – Snubber Line \***

A snubber line is utilized when the towed vessel has a large freeboard making it difficult to reach and disconnect the tow leg from the bow area.

**G. Snubber Connection - Tow Leg End (choose between 1 or 2 below)**

- 1. Hard Eye \_\_\_\_\_ (y/n - standard)
  - a. Light Duty s/s Thimble \_\_\_\_\_ (std for recreational lake applications)
  - b. Heavy Duty s/s Thimble \_\_\_\_\_ (std for commercial and ocean applications)
- 2. Soft Eye \_\_\_\_\_ (y/n – customer specified below)
  - a. Eye Splice Size \_\_\_\_\_ (18”, 24” are typical)
  - b. Chafe Guard \_\_\_\_\_ (y/n - covered eyes are recommended)

A soft eye is chosen if the towed vessel is put underway with the snubber still attached.

**H. Snubber**

- 1. Specify Length \_\_\_\_\_ (10ft is typical – customer specified)
- 2. Specify Material \_\_\_\_\_ (same material and diameter as tow leg - std)

**I. Snubber Connection – Bow (choose between 1 or 2 below)**

- 1. Hard Eye \_\_\_\_\_ (y/n - standard)
  - a. Light Duty s/s Thimble \_\_\_\_\_ (std for recreational lake applications)
  - b. Heavy Duty s/s Thimble \_\_\_\_\_ (std for commercial and ocean applications)
- 2. Soft Eye \_\_\_\_\_ (y/n – customer specified below)
  - a. Eye Splice Size \_\_\_\_\_ (18”, 24” are typical)
  - b. Chafe Guard \_\_\_\_\_ (y/n - covered eyes are recommended)

**J. Bow Hardware (choose from stainless steel hardware listed below)**

- 1. Bow Shackle \_\_\_\_\_ (y/n)
- 2. Bolted Safety Shackle \_\_\_\_\_ (y/n)
- 3. Swivel Eye Hook \_\_\_\_\_ (y/n)
- 4. Quick Release Snap Shackle \_\_\_\_\_ (y/n)
- 5. Trigger Release Shackle \_\_\_\_\_ (y/n)



Swivel Eye Hook and Bow Shackle



Quick Release Snap Shackle



Trigger Release Shackle

We will assist the customer in selecting the hardware that matches the W.L. of the line.

[www.denverrope.com](http://www.denverrope.com)

For customer service and inquiries please call John 303-809-7274 or email [john@denverrope.com](mailto:john@denverrope.com).

Please email the completed worksheet back to John of Denver Rope or can fax to 305-635-0530 attention Cari Valdes – Denver Rope.