



DENVER ROPE - DOCK LINES & MOORING LINES

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

3-STRAND NYLON							
Part Number	Nominal Diameter			Nominal Circumference		Tensile Strength	Color Code
	p/n prefix	inches	decimal	mm	inches	mm	pounds lb.
DL38	3/8"	0.375	9.5	1.2	29.9	3,700	Black = 1
DL12	1/2"	0.500	12.7	1.6	39.9	6,400	White = 8
DL58	5/8"	0.625	15.9	2.0	49.9	10,400	
DL34	3/4"	0.750	19.1	2.4	59.0	13,800	
DL78	7/8"	0.875	22.2	2.8	69.8	20,000	
DL1	1-0"	1.000	25.4	3.1	79.8	25,000	
DL114	1-1/4"	1.250	31.8	3.9	99.8	37,500	
DL112	1-1/2"	1.500	38.1	4.7	119.7	53,000	
DL2	2-0"	2.000	50.8	6.3	159.7	90,000	
DL212	2-1/2"	2.500	63.5	7.9	199.6	125,000	
DL3	3-0"	3.000	76.2	9.4	239.5	274,000	

Most common color is solid black and is the assumed default color. White is assumed in the larger diameters

Additional Solid Colors and Combinations require a Special Production Run at the discretion of the production mgr.

Typical turn-around splicing time for in-stock rope = 1-2 weeks + ship time

Typical turn-around for new rope production + splicing time = 4-5 weeks + ship time

PART NUMBER DEVELOPMENT => PART NUMBER + FOOTAGE TO THE NEAREST FOOT + COLOR CODE + DESCRIPTIONS

1-0" x 50ft - Black 3-Strand Nylon Dock Line => DL1 + 50 + 1 = DL1501 + Eye Length Size + Special Options

DL1501 Dock Line with a 10" Eye Splice

DL1501 Dock Line with a 12" Covered Eye Splice

DL1501 Dock Line with a 18" Covered Eye Splice on Each End

DL1501 Dock Line with a 24" Covered Eye Splice One End. Other End with a Heavy Duty Galvanized Thimble Splice

Not sure? Simply Describe the Dock Line in detail and how each end of the line is to be made up. Please email, call, and ask



DENVER ROPE - DOCK LINES & MOORING LINES

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

DOCK LINE SELECTION PROCESS

1. Choose Rope Diameter
2. Choose Rope Length. Note typical minimum DBN splicing length = 6ft. Otherwise 3-Strand Nylon is used
3. Choose Rope Color / Combination
4. Choose Loop / Eye Splice Size (10", 12", 18", 24", etc.). Measure your cleats (perform test fit) to determine what loop / eye size will work best to secure your boat. We assume the other end of the dock line is bitter.
5. Choose Optional Black Nylon Cordura Chafe Guard "Covered Eye". Additional locations upon request (i.e. chock protection). Chafe Guard is Recommended for Long Term Mooring applications.
6. Choose Quantity of Dock Lines for that Length
7. Repeat Selection Process for Each Set of Dock Lines (bow, stern, spring, mooring lines, houseboat shore lines, etc.)
8. 3-Strand Lines are NOT whipped at the splice throat and bitter end, but you may purchase whipping and select a separate whipping twine color for each set of dock lines.

Note: All lines are custom made-to-order and further customization can be specified for your application.

For customer service and inquiries please call John 303-809-7274 or email john@denverrope.com;
www.denverrope.com