



DENVER ROPE - ANCHOR LINES & MOORING LINES

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

3-STRAND NYLON							
Part Number	Nominal Diameter			Nominal Circumference		Tensile Strength	Color Code
	p/n prefix	inches	decimal	mm	inches	mm	pounds lb.
AL38	3/8"	0.375	9.5	1.2	29.9	3,700	Black = 1
AL12	1/2"	0.500	12.7	1.6	39.9	6,400	White = 8
AL58	5/8"	0.625	15.9	2.0	49.9	10,400	
AL34	3/4"	0.750	19.1	2.4	59.0	13,800	
AL78	7/8"	0.875	22.2	2.8	69.8	20,000	
AL1	1-0"	1.000	25.4	3.1	79.8	25,000	
AL114	1-1/4"	1.250	31.8	3.9	99.8	37,500	
AL112	1-1/2"	1.500	38.1	4.7	119.7	53,000	
AL2	2-0"	2.000	50.8	6.3	159.7	90,000	
AL212	2-1/2"	2.500	63.5	7.9	199.6	125,000	
AL3	3-0"	3.000	76.2	9.4	239.5	274,000	

Most common color is solid black and is the assumed default color. White is assumed in the larger diameters

Additional Solid Colors and Combinations require a Special Production Run at the discretion of the production mgr.

Typical turn-around splicing time for in-stock rope = 1-2 weeks + ship time

Typical turn-around for new rope production + splicing time = 4-5 weeks + ship time

PART NUMBER DEVELOPMENT => PART NUMBER + FOOTAGE TO THE NEAREST FOOT + COLOR CODE + DESCRIPTIONS

5/8" x 250ft - White 3-Strand Nylon Anchor Line => AL58+ 250 + 8 = AL582508 + Thimble Type (Galvanized STD) + Special Options
AL582508 Anchor Line

AL582508 Anchor Line with a Light Duty S/S Thimble Splice and a 1/2" S/S Bow Shackle

AL582508 Anchor Line with a Galvanized Heavy Duty Wire Rope Thimble Splice Each End

AL582508 Anchor Line with a 18" Covered Eye Splice One End. Other End with a Heavy Duty Galvanized Thimble Splice

Not sure? Simply Describe the Anchor Line in detail and how each end of the line is to be made up. Please email, call, and ask



DENVER ROPE - ANCHOR LINES & MOORING LINES

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

ANCHOR LINE SELECTION PROCESS

1. Choose Rope Diameter
2. Choose Rope Length. Note typical minimum DBN splicing length = 6ft. Otherwise 3-Strand Nylon is used
3. Choose Rope Color / Combination
4. Our anchor lines come STD with a galvanized thimble splice on one end (or optional Lt duty stainless steel). The thimble can be further specified as heavy duty (stainless steel or galvanized). We assume the other end of the anchor line is bitter.
5. Choose an optional stainless steel or galvanized Bow Shackle, Anchor Shackle, or Anchor Swivel.
6. Choose optional anchor chain (proof coil or windlass grade (G4 HT or BBB) & in stainless steel or galvanized)
7. Repeat Selection Process for each Anchor Line
8. 3-Strand Lines are NOT whipped at the splice throat and bitter end, but you may purchase whipping and select a separate whipping twine color for each set of dock lines.

Note: All lines are custom made-to-order and further customization can be specified for your application.

For customer service and inquiries please call John 303-809-7274 or email john@denverrope.com;

www.denverrope.com