

DENVER ROPE - BOAT LINE SELECTION GUIDE

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

	Boat Line Selection Guide								
		Dock Line Selection	Anchor Line Selection Guide						
Boat Length	Diameter	Stern & Bow Lines	Spring Lines	Short Lines	Length	Diameter	Mooring Pendant		
<= 19 ft	3/8"	(2) 10 ft	(2) 24 ft	(2) 10 ft	75 - 150 ft	3/8"	1/2"		
20 - 30 ft	1/2"	(2-4) 12 ft	(2) 30 ft	(2) 10 ft	75 - 150 ft	1/2"	5/8"		
31 - 40 ft	5/8"	(2-4) 15 ft	(2) 40 ft	(2) 10 ft	100 - 200 ft	1/2" - 5/8"	3/4" - 7/8"		
41 - 50 ft	3/4"	(2-4) 20 ft	(2) 50 ft	(2) 15 ft	100 - 200 ft	3/4" - 7/8"	1-0"		
51 - 60 ft	7/8"	(2-4) 25 ft	(2) 60 ft	custom	100 - 200 ft	1-0"	1-1/4"		
61 - 70 ft	1-0"	(2-4) 30 ft	(2) 70 ft	custom	>= 200 ft	1-0" - 1-1/4"	1-1/4" - 1-1/2"		
Houseboat	3/4"	(2-4) 15-20 ft	custom	(4-8) 8-10 ft	(4) 100 - 200 ft	3/4"	1-1/2" - 2-0"		
71 - 90 ft	1-0"	custom	custom	custom	custom	custom	custom		
91 - 110 ft	1-1/8"	custom	custom	custom	custom	custom	custom		
111 - 130 ft	1-1/4"	custom	custom	custom	custom	custom	custom		
131 - 150 ft	1-1/2"	custom	custom	custom	custom	custom	custom		
151 - 200 ft	1-3/4"	custom	custom	custom	custom	custom	custom		
201 - 300 ft	2-0"	custom	custom	custom	custom	custom	custom		
> 300 ft	custom	custom	custom	custom	custom	custom	custom		

These are suggestions only. Check with your boat manufacture / dealer / neighbor's / harbor master to help with your selection.

Verify the distance between your boat's cleats and the dock's cleats.

Expected weather conditions, windage, weight, and application (lake, ocean, MY, houseboat, qty of cleats, etc.) affect your line selection.

Having a set of back-up storm lines is recommended.

We are a custom made-to-order rigging shop so please customize your lines for what you need.



DENVER ROPE - DBN / HARDWARE STRENGTH GUIDE

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

NYLON DOUBLE BRAID (DBN) Single Leg Line			S/S Bow Shackle	S/S Safety Bolted Shackle	GALV Safety Bolted Shackle	S/S Swivel Eye Hook	S/S Spring - Harness Clip	Quick Release Snap Shackle	Trigger Release LB Shackle	Rope Connector c/w Spool, Shield, & Shackle	
Diamo	Diameter Tensile WLL 5:1		Note: If a thimble is used, the shackle needs to match the width /								
inches	mm	pounds	pounds	size of the thimble to match the diameter of the rope. 1-0" rope = 1-0" thimble = 1-0" shackle. Dry fit required.							
1/2"	13	7,300	1,460	3/8", 7/16"	3/8"	3/8"	5/16"	1/2", 1/2"	W2776	T20	SZ 1
5/8"	16	14,600	2,920	1/2"	7/16", 1/2"	7/16"	3/8"	na, 1/2"	W2776	T20	SZ 2
3/4"	19	19,000	3,800	1/2", 5/8"	1/2", 5/8"	1/2"	1/2"		W2776	T20	SZ 3
7/8"	22	28,100	5,620	3/4", 7/8"	5/8", 3/4"	1/2"			W2776	T30	SZ 4
1-0"	25	33,200	6,640	1-0"	3/4", 7/8"	5/8"			W2777	T30	SZ 4
1-1/4"	32	52,000	10,400	1-1/4"	1-0"	3/4"			W2778	T30	SZ 5
1-1/2"	38	74,000	14,800		1-1/4"	7/8"				T30	SZ 6
1-5/8"	41	92,100	18,420			1-0"				T40	SZ 6
1-3/4"	45	109,500	21,900			1-1/8"				T40	SZ 6
2-0"	51	129,700	25,940			1-1/4"				T50	SZ 7
2-1/4"	57	179,400	35,880			1-1/2"					SZ 7
2-1/2"	64	196,000	39,200			1-3/4"					SZ 8
2-5/8"	67	221,000	44,200			1-3/4"					SZ 8
2-3/4"	70	237,000	47,400			1-3/4"					SZ 9
3-0"	76	274,000	54,800			1-3/4"					SZ 9
3-1/4"	83	339,000	67,800		_	2-0"	_				SZ 9

These figures are for brand new rope. Age, wear, sunlight exposure, splices, and fraying will further reduce these figures over time

All hardware sizing is approximate where thimble size and rope thickness may require a larger shackle to fit properly

Heavy Duty Towing Thimbles are available to include NEWCO, Blue Line, NAVSEA, GN Rope Fittings, Rope Connectors, etc.

We also supply towing plates, wire rope assemblies, stud link chain, and additional hardware as required $\frac{1}{2}$

Additional fiber and rope construction styles are available

For customer service and inquiries please call John 303-809-7274 or email john@denverrope.com;

www.denverrope.com



DENVER ROPE

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

Diameter	Diameter	Diameter	Circumference	Circumference		
fractional	decimal					
inches	inches	mm	inches	mm		
1/8"	1/8" 0.125		0.4	10.0		
3/16"			0.6	15.0		
1/4"	0.25	6.4	0.8	20.0		
5/16"	0.3125	7.9	1.0	24.9		
3/8"	0.375	9.5	1.2	29.9		
7/16"	0.4375	11.1	1.4	34.9		
1/2"	0.5	12.7	1.6	39.9		
9/16"	0.5625	14.3	1.8	44.9		
5/8"	0.625	15.9	2.0	49.9		
3/4"	0.75	19.1	2.4	59.9		
7/8"	0.875	22.2	2.8	69.8		
1-0"	1.0	25.4	3.1	79.8		
1-1/8"	1.1875	30.2	3.7	94.8		
1-1/4"	1.25	31.8	3.9	99.8		
1-1/2"	1.5	38.1	4.7	119.7		
1-5/8"	1.625	41.3	5.1	129.7		
1-3/4"	1.75	44.5	5.5	139.7		
2-0"	2.0	50.8	6.3	159.7		
2-1/8"	2.2	55.6	6.9	174.6		
2-1/4"	2.25	57.2	7.1	179.6		
2-1/2"	2.5	63.5	7.9	199.6		
2-5/8"	2.625	66.7	8.2	209.6		
2-3/4"	2.75	69.9	8.6	219.5		
3-0"	3.0	76.2	9.4	239.5		
3-1/4"	3.25	82.6	10.2	259.4		
3-1/2"	3.5	88.9	11.0	279.4		
3-5/8"	3.625	92.1	11.4	289.4		
3-3/4"	3.75	95.3	11.8	299.4		
4-0"	4.0	101.6	12.6	319.3		
4-1/4"	4.25	108.0	13.4	339.3		
4-1/2"	4.5	114.3	14.1	359.2		
4-5/8"	4.625	117.5	14.5	369.2		
4-3/4"	4.75	120.7	14.9	379.2		
5-0"	5.0	127.0	15.7	399.1		



DENVER ROPE

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

Conversion Factors and Information

1 inch = 25.4 mm

12 inches = 1 foot

1 foot = 304.8 mm

1 meter = 3.28 ft

Circumference of a Circle

 $Circular = PI \times Diameter$

Weight

1 Pound = 0.4536 kG

1 kG = 2.2046 lbs

Force

1 Newton = 0.2248 lbs

1 kN = 224.8 lbs

Standard Hawser Lengths

 $50~{\rm ft}$ / $100~{\rm ft}$ / $300~{\rm ft}$ / $600~{\rm ft}$ / $720~{\rm ft}$ / $900~{\rm ft}$ / Custom

Where 1 Fathom = 6 feet

Minimum Breaking Strength (MBS) to Working Load Limit (WLL)

WLL for Very Conservative = MBS/10

WLL for Standard Conservative = MBS/5 (Denver Rope Selection)

WLL for Less Conservative = MBS/3

WLL = Engineered Calculation

MBS = Tensile Strength

For customer service and inquiries please call John 303-809-7274 or email john@denverrope.com; www.denverrope.com