



ANCHOR RODE - ROPE & CHAIN GUIDE

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

WINDLASS - NYLON 3-STRAND TWISTED			
Diameter	Diameter	Tensile Strength	Working Load
inches	mm	pounds	pounds
1/2"	13	6,400	1,280
9/16"	14	7,900	1,580
5/8"	16	10,400	2,080
3/4"	19	13,800	2,760

These figures are for brand new rope. Age, wear, sunlight exposure, splices, and knots will further reduce these figures over time.

WINDLASS - NYLON 8-PLAIT			
Diameter	Diameter	Tensile Strength	Working Load
inches	mm	pounds	pounds
3/8"	9.5	4,000	1,000
1/2"	13	8,300	2,075
9/16"	14	9,200	2,300
5/8"	16	12,200	3,050
3/4"	19	17,000	4,250
1-0"	25	24,840	6,210

These figures are for brand new rope. Age, wear, sunlight exposure, splices, and knots will further reduce these figures over time.

Galvanized WINDLASS CHAIN - G4 HIGH TEST			
Diameter	Diameter	Tensile Strength	Working Load
inches	mm	pounds	pounds
1/4"	6.4	-	2,600
5/16"	8	-	3,900
3/8"	9.5	-	5,400
7/16"	11	-	7,200
1/2"	13	-	9,200
5/8"	16	-	13,000

ACCO Grade 43 Premium Hot Galvanized Chain used for Windlasses and Pleasure Marine. High test carbon steel provides both high tensile strength and resistance to wear. ISO short link dimensions. Best weight to W.L. ratio. Imported G4 HT anchor chain also available.

Galvanized WINDLASS CHAIN - BBB			
Diameter	Diameter	Tensile Strength	Working Load
inches	mm	pounds	pounds
1/4"	6.4	-	1,300
5/16"	8	-	1,900
3/8"	9.5	-	2,650
7/16"	11	-	-
1/2"	13	-	4,500
5/8"	16	-	-

ACCO Grade 30 Brand BBB Hot Galvanized Chain. Used for Windlasses and Pleasure Marine. A low carbon steel, general purpose chain, with short compact link. The short link dimensions makes it more flexible and ideally suited as anchor chain.

For customer service and inquiries please call John 303-809-7274 or email john@denverrope.com;
www.denverrope.com



ANCHOR RODE - ROPE & CHAIN GUIDE

The Best Custom Boat Lines, Custom Colored Ropes, & Special Assemblies made to Your Specifications

Stainless WINDLASS CHAIN - G4 HIGH TEST			
Diameter	Diameter	Tensile Strength	Working Load
inches	mm	pounds	pounds
1/4"	6.4	-	2,000
5/16"	8	-	2,400
3/8"	9.5	-	3,550
1/2"	13	-	6,500

Suncor Grade 43 Stainless Steel Anchor Chain type 316 with ISO short links. Imported S/S G4 HT anchor chain also available.

Stainless WINDLASS CHAIN - BBB			
Diameter	Diameter	Tensile Strength	Working Load
inches	mm	pounds	pounds
1/4"	6.4	-	2,000
5/16"	8	-	2,400
3/8"	9.5	-	3,550
1/2"	13	-	6,500

Suncor Grade 30 Stainless Steel Anchor Chain type 316. Compliant with DIN 766.

ACCO Metric Windlass Chain => We do offer, with extended lead times, Galvanized Grade 40 Metric Chain compliant with DIN 766 or DIN 818-3

For customer service and inquiries please call John 303-809-7274 or email john@denverrope.com;
www.denverrope.com